

ELECTRIC DRIVE SELF CLEANING WATER FILTER

FED350

FED350 · FED · DN 350 · Electric drive

Electric motor drive automatic filter. DN350. Flow rate 900 m³/h.

TECHNICAL DAT ASHEET



SCAN FOR PRODUCT PAGE

filtaworx.com/products/automatic-filters/fed350



KEY FEATURES

- Electric Gear Motor Drive
- Precise Backwash Control
- Self-Reversing Drive Shaft
- Suction Nozzle Cleaning
- Wide Pressure Range: 0.5–16 bar
- PLC Controller Integration

SPECIFICATIONS

Drive Type	Electric
Filter Size	DN350
Flow Rate	900 m ³ /h
Filtration Area	12,170 cm ²
Operating Pressure	0.5–16 bar
Max Temperature	65 °C
Rinse Cycle	15–17 seconds

02 · DIMENSIONS

Dimensions

TABLE 1 Data & Weights

Model	DN	Flowrate	Filter area	Weight (Std)	Weight (HP)
FED350	DN350	900 m ³ /h	12,170 cm ²	285 kg	595 kg (full)

TABLE 2 Dimensions

Dimension	Value
Inlet / Outlet	DN350 (14")
Body Ø	406 mm
Centre distance	1,270 mm
Body O/A length	2,531 mm
Filtration area	12,170 cm ²
Flow rate	900 m ³ /h (3,963 gpm)


TABLE 3 Shipping & weights

Item	Value
Packed dimensions (L x W x H)	340 x 63 x 83 cm
Shipping volume	1.3 m ³
Weight — standard	290 kg (640 lb)
Weight — high pressure	310 kg (685 lb)

03 • PERFORMANCE

Performance

PERFORMANCE Pressure Drop vs Flow



Curves: $dp(q) = r \cdot q^2$ across available screen sizes. Source per screen — 30µm : estimated · 50µm : estimated · 100µm : estimated · 150µm : estimated · 200µm : estimated · 300µm : estimated · 400µm : estimated · 800µm : estimated.

Filtaworx · Australian manufacturer of automatic self-cleaning filters

filtaworx.com/products/automatic-filters/fed350