

AUTOMATIC SELF CLEANING WATER FILTER

FW050

FW050 · FW · DN 50 · Hydraulic drive

Compact automatic filter. DN50. Flow rate 25 m³/h. Hydraulic drive.

TECHNICAL DATASHEET



SCAN FOR PRODUCT PAGE

filtaworx.com/products/automatic-filters/fw050



KEY FEATURES

- No External Power Required
- Continuous Flow During Backwash
- Compact Design
- Moulded Plastic Screen
- 5–7 Second Rinse Cycle
- BSP and Flanged Connections
- PN10/PN16 Pressure Rating
- SS304/SS316 Options

SPECIFICATIONS

Drive Type	Hydraulic
Filter Size	DN50
Flow Rate	25 m ³ /h
Filtration Area	1,220 cm ²
Operating Pressure	2.0–10 bar
Max Temperature	65 °C
Rinse Cycle	5–7 seconds

02 • DIMENSIONS

Dimensions

TABLE 1 Data & Weights

Model	DN	Flowrate	Filter area	Weight (Std)	Weight (HP)
FW050	DN50	25 m ³ /h	1,220 cm ²	25 kg	38 kg

TABLE 2 Dimensions

Dimension	Value
Inlet / Outlet	DN50 (2")
Body Ø	273 mm
Centre distance	—
Body O/A length	298 mm
Filtration area	1,220 cm ²
Flow rate	25 m ³ /h (110 gpm)


TABLE 3 Shipping & weights

Item	Value
Packed dimensions (L x W x H)	71 x 52 x 57 cm
Shipping volume	0.21 m ³
Weight — standard	25 kg (55 lb)
Weight — high pressure	38 kg (84 lb)

03 • PERFORMANCE

Performance

PERFORMANCE Pressure Drop vs Flow



Curves: $dp(q) = r \cdot q^2$ across available screen sizes. Source per screen — 30µm : estimated · 50µm : estimated · 100µm : estimated · 150µm : estimated · 200µm : estimated · 300µm : estimated · 400µm : estimated · 800µm : estimated.

Filtaworx · Australian manufacturer of automatic self-cleaning filters

filtaworx.com/products/automatic-filters/fw050