

AUTOMATIC SELF CLEANING WATER FILTER

FW150

FW150 · FW · DN 150 · Hydraulic drive

Large piston-driven automatic filter. DN150. Flow rate 180 m³/h. Hydraulic drive.

TECHNICAL DATASHEET



SCAN FOR PRODUCT PAGE

filtaworx.com/products/automatic-filters/fw150



KEY FEATURES

- Hydraulic Drive – No External Power
- Suction Scanning Technology
- Continuous Flow
- 15–17 Second Flush Cycle
- PN10/PN16 Pressure Rating
- SS304/SS316 Options

SPECIFICATIONS

Drive Type	Hydraulic
Filter Size	DN150
Flow Rate	180 m ³ /h
Filtration Area	5,600 cm ²
Operating Pressure	2.0–10 bar
Max Temperature	65 °C
Rinse Cycle	15–17 seconds

02 • DIMENSIONS

Dimensions

TABLE 1 Data & Weights

Model	DN	Flowrate	Filter area	Weight (Std)	Weight (HP)
FW150	DN150	180 m ³ /h	5,600 cm ²	105 kg	131 kg

TABLE 2 Dimensions

Dimension	Value
Inlet / Outlet	DN150 (6")
Body Ø	325 mm
Centre distance	900 mm
Body O/A length	1,455 mm
Filtration area	5,600 cm ²
Flow rate	180 m ³ /h (793 gpm)


TABLE 3 Shipping & weights

Item	Value
Packed dimensions (L x W x H)	220 x 56 x 71 cm
Shipping volume	0.88 m ³
Weight — standard	105 kg (235 lb)
Weight — high pressure	131 kg (290 lb)

03 • PERFORMANCE

Performance

PERFORMANCE Pressure Drop vs Flow



Curves: $dp(q) = r \cdot q^2$ across available screen sizes. Source per screen — 30µm : estimated · 50µm : estimated · 100µm : estimated · 150µm : estimated · 200µm : estimated · 300µm : estimated · 400µm : estimated · 800µm : estimated.

Filtaworx · Australian manufacturer of automatic self-cleaning filters

filtaworx.com/products/automatic-filters/fw150